8212-4

POTENTIAL HAZARDOUS WASTE SITE
IDENTIFICATION AND PRELIMINARY ASSESSMENT

EPA

REGION	SITE NUMBER (to be assigned by HQ)
6	TX 1074

NOTE: This form is completed for each potential hazardous waste site to help set priorities for site inspection. The information submitted on this form is based on available records and may be updated on subsequent forms as a result of additional inquiries and on-site inspections.

GENERAL INSTRUCTIONS: Complete Sections I and III through X as completely as possible before Section II *(Preliminary Assessment)*. File this form in the Regional Hazardous Waste Log File and submit a copy to: U.S. Environmental Protection Agency; Site Tracking System; Hazardous Waste Enforcement Task Force *(EN-335)*; 401 M St., SW; Washington, DC 20460.

I. SITE IDENTIFICATION TXD008092793

A. SITE NAME	B. STREET (or other identifier)		
Dow Chemical Co. - TX Div.- Plant B	Hwy 288 (Going East to West until the end) B-1226		
C. CITY	**D. STATE**	**E. ZIP CODE**	**F. COUNTY NAME**
Freeport	TX	77541	Brazoria

G. OWNER/OPERATOR *(If known)*
1. NAME: Dow Chemical Co.
C.W. Evans - Env. Manager
x-Ref SA Vol 1 # 1
2. TELEPHONE NUMBER: 713/238-1227, 713/238-2475

H. TYPE OF OWNERSHIP
☐ 1. FEDERAL ☐ 2. STATE ☐ 3. COUNTY ☐ 4. MUNICIPAL ☒ 5. PRIVATE ☐ 6. UNKNOWN

I. SITE DESCRIPTION Large chemical manufacturing facility; site has been active since 1941. Contains: (4) inactive landfills; (12) inactive ponds; inactive incinerator, inactive injection well (2) inactive storage tanks.

J. HOW IDENTIFIED *(i.e., citizen's complaints, OSHA citations, etc.)*	K. DATE IDENTIFIED *(mo., day, & yr.)*
TDWR Files	4/22/80

L. PRINCIPAL STATE CONTACT
1. NAME: Tom Kearns, TDWR #7
2. TELEPHONE NUMBER: 713/479-5981

II. PRELIMINARY ASSESSMENT *(complete this section last)*

A. APPARENT SERIOUSNESS OF PROBLEM
☐ 1. HIGH ☒ 2. MEDIUM ☐ 3. LOW ☐ 4. NONE ☐ 5. UNKNOWN

B. RECOMMENDATION
☐ 1. NO ACTION NEEDED *(no hazard)*
☒ 2. SITE INSPECTION NEEDED
a. TENTATIVELY SCHEDULED FOR: _____
b. WILL BE PERFORMED BY: _____
☐ 3. IMMEDIATE SITE INSPECTION NEEDED
a. TENTATIVELY SCHEDULED FOR: _____
b. WILL BE PERFORMED BY: _____
☐ 4. SITE INSPECTION NEEDED *(low priority)*

RECEIVED MAR 25 1983

C. PREPARER INFORMATION
1. NAME: Gerard A. Gallagher III - FIT
2. TELEPHONE NUMBER: 214/742-6601
3. DATE *(mo., day, & yr.)*: 2/28/83

III. SITE INFORMATION

A. SITE STATUS
☒ 1. ACTIVE *(Those industrial or municipal sites which are being used for waste treatment, storage, or disposal on a continuing basis, even if intermittently.)*
☐ 2. INACTIVE *(Those sites which no longer receive wastes.)*
☐ 3. OTHER *(specify)*: _____ *(Those sites that include such incidents like "midnight dumping" where no regular or continuing use of the site for waste disposal has occurred.)*
Both active and inactive facilities

B. IS GENERATOR ON SITE?
☐ 1. NO ☒ 2. YES *(specify generator's four-digit SIC Code)*: _____

SUPERFUND FILE

C. AREA OF SITE *(in acres)*	D. IF APPARENT SERIOUSNESS OF SITE IS HIGH, SPECIFY COORDINATES	
	1. LATITUDE *(deg.—min.—sec.)*	2. LONGITUDE *(deg.—min.—sec.)*
75 acres	28°59'00" N	95°23'30" W

DEC 30 1992 REORGANIZED

E. ARE THERE BUILDINGS ON THE SITE?
☐ 1. NO ☒ 2. YES *(specify)*: Chemical process units nearby

REVIEWED BY (AGENCY) DATE 4-1-83

T2070-2 (10-79)

Continue On Reverse

924078

Continued From Front

IV. CHARACTERIZATION OF SITE ACTIVITY

Indicate the major site activity(ies) and details relating to each activity by marking 'X' in the appropriate boxes.

A. TRANSPORTER	B. STORER	C. TREATER	D. DISPOSER
1. RAIL	1. PILE	1. FILTRATION	X 1. LANDFILL
2. SHIP	2. SURFACE IMPOUNDMENT	X 2. INCINERATION	2. LANDFARM
3. BARGE	X 3. DRUMS	3. VOLUME REDUCTION	3. OPEN DUMP
4. TRUCK	X 4. TANK, ABOVE GROUND	X 4. RECYCLING/RECOVERY	X 4. SURFACE IMPOUNDMENT
5. PIPELINE	5. TANK, BELOW GROUND	5. CHEM./PHYS. TREATMENT	5. MIDNIGHT DUMPING
X 6. OTHER (specify): UNKNOWN	6. OTHER (specify):	X 6. BIOLOGICAL TREATMENT	X 6. INCINERATION
		7. WASTE OIL REPROCESSING	X 7. UNDERGROUND INJECTION
		8. SOLVENT RECOVERY	8. OTHER (specify):
		9. OTHER (specify):	

E. SPECIFY DETAILS OF SITE ACTIVITIES AS NEEDED

See Attachment II

V. WASTE RELATED INFORMATION

A. WASTE TYPE

☐ 1. UNKNOWN ☒ 2. LIQUID ☒ 3. SOLID ☒ 4. SLUDGE ☐ 5. GAS

B. WASTE CHARACTERISTICS

☐ 1. UNKNOWN ☒ 2. CORROSIVE ☐ 3. IGNITABLE ☐ 4. RADIOACTIVE ☐ 5. HIGHLY VOLATILE
☒ 6. TOXIC ☐ 7. REACTIVE ☒ 8. INERT ☐ 9. FLAMMABLE

☐ 10. OTHER (specify):

C. WASTE CATEGORIES

1. Are records of wastes available? Specify items such as manifests, inventories, etc. below.

Yes

2. Estimate the amount(specify unit of measure) of waste by category; mark 'X' to indicate which wastes are present.

a. SLUDGE	b. OIL	c. SOLVENTS	d. CHEMICALS	e. SOLIDS	f. OTHER
AMOUNT: UNKNOWN	AMOUNT: UNKNOWN	AMOUNT: UNKNOWN	AMOUNT: UNKNOWN	AMOUNT: UNKNOWN	AMOUNT: NONE
UNIT OF MEASURE:	UNIT OF MEASURE:	UNIT OF MEASURE:	UNIT OF MEASURE:	UNIT OF MEASURE:	UNIT OF MEASURE:
(1) PAINT, PIGMENTS	X (1) OILY WASTES	X (1) HALOGENATED SOLVENTS	X (1) ACIDS	(1) FLYASH	X (1) LABORATORY PHARMACEUT.
(2) METALS SLUDGES	(2) OTHER (specify):	X (2) NON-HALOGNTD. SOLVENTS	(2) PICKLING LIQUORS	X (2) ASBESTOS	(2) HOSPITAL
(3) POTW		(3) OTHER (specify):	X (3) CAUSTICS	(3) MILLING/ MINE TAILINGS	(3) RADIOACTIVE
(4) ALUMINUM SLUDGE			(4) PESTICIDES	(4) FERROUS SMLTG. WASTES	(4) MUNICIPAL
X (5) OTHER (specify): Polychlorinated Magnesium Cell Styrene tars	Sludges		(5) DYES/INKS	(5) NON-FERROUS SMLTG. WASTES	(5) OTHER (specify):
			(6) CYANIDE	X (6) OTHER (specify): Plant trash	
			X (7) PHENOLS		
			(8) HALOGENS		
			X (9) PCB		
			X (10) METALS		
			(11) OTHER (specify)		

Continue On Page 3

Continued From Page 2

V. WASTE RELATED INFORMATION (continued)

3. LIST SUBSTANCES OF GREATEST CONCERN WHICH MAY BE ON THE SITE (place in descending order of hazard).

See Attachment IV.

4. ADDITIONAL COMMENTS OR NARRATIVE DESCRIPTION OF SITUATION KNOWN OR REPORTED TO EXIST AT THE SITE.

It is unknown whether all inactive waste disposal facilities have been properly closed out. There is also some confusion concerning which wastes are exclusive to which plant. A FIT inspection is recommended.

VI. HAZARD DESCRIPTION

A. TYPE OF HAZARD	B. POTENTIAL HAZARD (mark 'X')	C. ALLEGED INCIDENT (mark 'X')	D. DATE OF INCIDENT (mo., day, yr.)	E. REMARKS
1. NO HAZARD				
2. HUMAN HEALTH				
3. NON-WORKER INJURY/EXPOSURE				
4. WORKER INJURY				
5. CONTAMINATION OF WATER SUPPLY				
6. CONTAMINATION OF FOOD CHAIN				
7. CONTAMINATION OF GROUND WATER				
8. CONTAMINATION OF SURFACE WATER				
9. DAMAGE TO FLORA/FAUNA				
10. FISH KILL				
11. CONTAMINATION OF AIR				
12. NOTICEABLE ODORS				
13. CONTAMINATION OF SOIL				
14. PROPERTY DAMAGE				
15. FIRE OR EXPLOSION				
16. SPILLS/LEAKING CONTAINERS/ RUNOFF/STANDING LIQUIDS				
17. SEWER, STORM DRAIN PROBLEMS				
18. EROSION PROBLEMS				
19. INADEQUATE SECURITY				
20. INCOMPATIBLE WASTES				
21. MIDNIGHT DUMPING				
22. OTHER (specify):				Insufficient information to determine potential hazard.

Continued From Front

VII. PERMIT INFORMATION

A. INDICATE ALL APPLICABLE PERMITS HELD BY THE SITE.

- [X] 1. NPDES PERMIT
- [X] 2. SPCC PLAN
- [X] 3. STATE PERMIT (specify): 30106
- [X] 4. AIR PERMITS
- [ ] 5. LOCAL PERMIT
- [ ] 6. RCRA TRANSPORTER
- [ ] 7. RCRA STORER
- [ ] 8. RCRA TREATER
- [ ] 9. RCRA DISPOSER
- [ ] 10. OTHER (specify):

B. IN COMPLIANCE?

- [ ] 1. YES
- [ ] 2. NO
- [XX] 3. UNKNOWN

4. WITH RESPECT TO (list regulation name & number):

VIII. PAST REGULATORY ACTIONS

- [ ] A. NONE
- [ ] B. YES (summarize below)

UNKNOWN

IX. INSPECTION ACTIVITY (past or on-going)

- [ ] A. NONE
- [ ] B. YES (complete items 1, 2, 3, & 4 below)

1. TYPE OF ACTIVITY	2. DATE OF PAST ACTION (mo., day, & yr.)	3. PERFORMED BY: (EPA/State)	4. DESCRIPTION
Inspection	9/28/82	TDWR	RCRA Compliance Inspection
Annual Inspection	9/20/79	TDWR	
Record Search	1/26/83	FIT	

X. REMEDIAL ACTIVITY (past or on-going)

- [ ] A. NONE
- [ ] B. YES (complete items 1, 2, 3, & 4 below)

1. TYPE OF ACTIVITY	2. DATE OF PAST ACTION (mo., day, & yr.)	3. PERFORMED BY: (EPA/State)	4. DESCRIPTION
UNKNOWN			

NOTE: Based on the information in Sections III through X, fill out the Preliminary Assessment (Section II) information on the first page of this form.

ATTACHMENT I

JONES CREEK QUADRANGLE
TEXAS-BRAZORIA CO.
7.5 MINUTE SERIES (TOPOGRAPHIC)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

DOW CHEMICAL U.S.A. ATTACHMENT II

TEXAS DIVISION
FREEPORT, TEXAS 77541

July 8, 1981

Mr. Minor Hibbs
Texas Dept. of Water Resources
P. O. Box 13087
Capitol Station
Austin, TX 78711

Dear Mr. Hibbs:

Attached are closure plans for two hazardous waste storage tanks and an incinerator that we have been operating under 40 CFR Part 265. Both tanks and the incinerator are included in our TDWR application for a hazardous waste permit and the EPA Part A. The tank in the B-4600 Block is listed in our TDWR Solid Waste Registration, #30106, and the incinerator is included in those facilities in the "incinerator area, Dow B-3".

We would appreciate your prompt attention to this matter as we anticipate other uses for the tanks and we will install a more modern incinerator on the site of the old one.

Sincerely,

Larry Bone

Larry I. Bone
Environmental Services

cgc

Attachments

SITE DESCRIPTION

Make additional comments or narrative description of situation known or reported to exist at the site based on file review. Include dates and description of any incidents documented in file.

The company began closing the Twelve Ponds containing chlorinated hydrocarbons in 1973. To date, all but two have been covered and closed. The chlorinated material was incinerated in the thermal oxidation unit.

A Sept. 17, 1979 IOM indicated the possibility of an unpermitted discharge from the B-1 site containing high chlorides. A similar possibility was raised in an Oct. 6, 1977 IOM and again on Aug. 25, 1977.

Table III-4 Hazardous Waste Facility Components List

Revised Replaced 9-10-82 TX1066 ATTACHMENT III

Facility Component Name	TDWR Seq. No.	Status: Inactive	Active	Proposed	Design Capacity: (cu yds)	(gal)	(lbs)	Number of Years Utilized	Date In Service
A-100 Block Landfill		X					1,000,000	5	1945-50
Verbal Description: First landfill in the Texas Division; Caustic wastes and other process wastes were disposed of at this site, along with lumber, trash and drummed materials.									
Disposal Area (A-41 Block)		X					1,253,300,000	20	1953-73
Verbal Description: A 34 acre landfill used to bury magnesium sludge, general trash and lumber, R-cake from the mag process, solids from riverwater treating, and miscellaneous organics. Radioactive wastes were also disposed of in this area under license.									
A-2 Disposal Are (6 pits)		X					56,010,000	6	1970-76
Verbal Description: The A-2 site (30 acres) was a series of six earthen pits (150' x 200' x 10') used to impound chlorinated hydrocarbons. In 1975 Dow began removing the chlorinated hydrocarbons and using them as feedstock for our Thermal Oxidizer to produce HCl for the production of magnesium.									
B-1 Disposal Area (12 pits)		X					164,200,000	8	1973-80
Verbal Description: In 1975, we began removing chlorinated hydrocarbons and using them as feedstock for our Thermal Oxidizer to produce HCl for the production of magnesium. The top water from the pits was returned to the waste treatment plant. The emptied ponds are filled with construction rubble and covered with clay. A 10-acre tract was used as a landfill to dispose of drums containing resins, waxes, and chlorinated materials.									
Site B-2		X					220,000,000	29	1944-73
Verbal Description: Two 3 acre lagoons which impound approximately 22 million gallons of styrene tars. Dow anticipates recovering these tars at some future date.									
A-27 Block		X					200,000		1948-52
Verbal Description: Area used between 1948 and 1952 for construction debris, magnesium sludge and other process wastes.									

Facility Component Name	TDWR Seq. No.	Status: Inactive	Active	Proposed	Design Capacity: (cu yds)	(gal)	(lbs)	Number of Years Utilized	Date In Servic
WDW-59		X					26,000,000	3	1970-7

Brief Description: Plant "B" Disposal Well #1 is located in the B-1700 block and was permitted 8/69 to dispose of aqueous solution of inorganic and organic wastes from the glycerine plant. Wastes were injected between 5778'-5864'. The well was plugged 3/77 with 2535 cubic feet of cement.

WDW-71		X					3,800,000	4	1971-7

Brief Description: Plant "B" Disposal Well #2, located in the B-6200 Block, permitted in 1971 to dispose of aqueous solutions of inorganic and organic wastes from the epoxy plant. Wastes were injected between 6200'-6400'. The well was plugged 11/79.

WDW-81		X					12,000,000	3	1971-7

Brief Description: Plant "A" Disposal Well #1, located in the A-38 Block, permitted in 1971 to dispose of aqueous solutions of inorganic and organic wastes from the glycol A and ethylene dichloride plants. Wastes were injected between 6295'-6356'. The well was plugged 12/79.

B-4 Incinerator Area ACTIVE			X	X			2.0 million/Mo.		

Brief Description: Consists of 2 scrubberburners to burn chlorinated hydrocarbons and two incinerators used to burn gels and solvents, storage tanks, a spill cleanup facility and drum washing unit. Two additional solids incinerators are being installed to burn paper, wood, trash, plastic foams, polywax, non-chlorinated resins, ion-exchange resins, latex solids, etc. to be completed in 1981. Additional liquids incinerator is being built to replace existing burners and incinerate waste oils, non-chlorinated solvents, amines, organic acids and other liquid burnable wastes. The liquid incinerator will also be completed in 1981.

Brief Description:

B-5 Landfill ACTIVE			X				880,000,000*	0	198(

Brief Description: A 10-acre landfill for the disposal of hazardous wastes according to RCRA defintion. This landfill will begin accepting wastes August, 1980.

*2000 acre-ft

ATTACHMENT IV

(2) It is not a liquid and is capable, under standard temperature and pressure, of causing fire through friction, absorption of moisture or spontaneous chemical changes and, when ignited, burns so vigorously and persistently that is creates a hazard.

(3) It is an ignitable compressed gas as defined in 49 CFR 173.300 and as determined by the test methods described in that regulation or equivalent test methods approved by the Administrator under §§ 260.20 and 260.21.

(4) It is an oxidizer as defined in 49 CFR 173.151.

(b) A solid waste that exhibits the characteristic of ignitability, but is not listed as a hazardous waste in Subpart D, has the EPA Hazardous Waste Number of D001.

§ 261.22 Characteristic of corrosivity.

(a) A solid waste exhibits the characteristic of corrosivity if a representative sample of the waste has either of the following properties:

(1) It is aqueous and has a pH less than or equal to 2 or greater than or equal to 12.5, as determined by a pH meter using either the test method specified in the "Test Methods for the Evaluation of Solid Waste, Physical/Chemical Methods" [2] (also described in "Methods for Analysis of Water and Wastes" EPA 600/4–79–020, March 1979), or an equivalent test method approved by the Administrator under the procedures set forth in §§ 260.20 and 260.21.

(2) It is a liquid and corrodes steel (SAE 1020) at a rate greater than 6.35 mm (0.250 inch) per year at a test temperature of 55°C (130°F) as determined by the test method specified in NACE (National Association of Corrosion Engineers) Standard TM–01–69 [3] as standardized in "Test Methods for the Evaluation of Solid Waste, Physical/Chemical Methods," or an equivalent test method approved by the Administrator under the procedures set forth in §§ 260.20 and 260.21.

(b) A solid waste that exhibits the characteristic of corrosivity, but is not listed as a hazardous waste in Subpart D, has the EPA Hazardous Waste Number of D002.

[2] This document is available from Solid Waste Information, U.S. Environmental Protection Agency, 26 W. St. Clair Street, Cincinnati, Ohio 45268.

[3] The NACE Standard is available from the National Association of Corrosion Engineers, P.O. Box 986, Katy, Texas 77450.

§ 261.23 Characteristic of reactivity.

(a) A solid waste exhibits the characteristic of reactivity if a representative sample of the waste has *any* of the following properties:

(1) It is normally unstable and readily undergoes violent change without detonating.

(2) It reacts violently with water.

(3) It forms potentially explosive mixtures with water.

(4) When mixed with water, it generates toxic gases, vapors or fumes in a quantity sufficient to present a danger to human health or the environment.

(5) It is a cyanide or sulfide bearing waste which, when exposed to pH conditions between 2 and 12.5, can generate toxic gases, vapors or fumes in a quantity sufficient to present a danger to human health or the environment.

(6) It is capable of detonation or explosive reaction if it is subjected to a strong initiating source or if heated under confinement.

(7) It is readily capable of detonation or explosive decomposition or reaction at standard temperature and pressure.

(8) It is a forbidden explosive as defined in 49 CFR 173.51, or a Class A explosive as defined in 49 CFR 173.53 or a Class B explosive as defined in 49 CFR 173.88.

(b) A solid waste that exhibits the characteristic of reactivity, but is not listed as a hazardous waste in Subpart D, has the EPA Hazardous Waste Number of D003.

§ 261.24 Characteristic of EP Toxicity.

(a) A solid waste exhibits the characteristic of EP toxicity if, using the test methods described in Appendix II or equivalent methods approved by the Administrator under the procedures set forth in §§ 260.20 and 260.21, the extract from a representative sample of the waste contains any of the contaminants listed in Table I at a concentration equal to or greater than the respective value given in that Table. Where the waste contains less than 0.5 percent filterable solids, the waste itself, after filtering, is considered to be the extract for the purposes of this section.

(b) A solid waste that exhibits the characteristic of EP toxicity, but is not listed as a hazardous waste in Subpart D, has the EPA Hazardous Waste Number specified in Table I which corresponds to the toxic contaminant causing it to be hazardous.

Table I.—Maximum Concentration of Contaminants for Characteristic of EP Toxicity—Continued

EPA hazardous waste number	Contaminant	Maximum concentration (milligrams per liter)
D004	Arsenic	5.0
D005	Barium	100.0
D006	Cadmium	1.0
D007	Chromium	5.0
D008	Lead	5.0
D009	Mercury	0.2
D010	Selenium	1.0
D011	Silver	5.0
D012	Endrin (1,2,3,4,10,10-hexachloro-1,7-epoxy-1,4,4a,5,6,7,8,8a-octahydro-1,4-endo, endo-5,8-dimethano naphthalene.	0.02
D013	Lindane (1,2,3,4,5,6-hexachlorocyclohexane, gamma isomer.	0.4
D014	Methoxychlor (1,1,1-Trichloro-2,2-bis [p-methoxyphenyl]ethane).	10.0
D015	Toxaphene ($C_{10}H_{10}Cl_8$, Technical chlorinated camphene, 67–69 percent chlorine).	0.5
D016	2,4-D, (2,4-Dichlorophenoxyacetic acid).	10.0
D017	2,4,5-TP Silvex (2,4,5-Trichlorophenoxypropionic acid).	1.0

Subpart D—Lists of Hazardous Wastes

§ 261.30 General.

(a) A solid waste is a hazardous waste if it is listed in this Subpart, unless it has been excluded from this list under §§ 260.20 and 260.22.

(b) The Administrator will indicate his basis for listing the classes or types of wastes listed in this Subpart by employing one or more of the following Hazard Codes:

Ignitable Waste	(I)
Corrosive Waste	(C)
Reactive Waste	(R)
EP Toxic Waste	(E)
Acute Hazardous Waste	(H)
Toxic Waste	(T)

Appendix VII identifies the constituent which caused the Administrator to list the waste as an EP Toxic Waste (E) or Toxic Waste (T) in §§ 261.31 and 261.32.

(c) Each hazardous waste listed in this Subpart is assigned an EPA Hazardous Waste Number which precedes the name of the waste. This number must be used in complying with the notification requirements of Section 3010 of the Act and certain recordkeeping and reporting requirements under Parts 262 through 265 and Part 122 of this Chapter.

(d) Certain of the hazardous wastes listed in § 261.31 or § 261.32 have exclusion limits that refer to § 261.5(c)(5).

§ 261.31 Hazardous waste from nonspecific sources.

Industry and EPA hazardous waste No.	Hazardous waste	Hazard code
Generic:		
F001	The spent halogenated solvents used in degreasing, tetrachloroethylene, trichloroethylene, methylene chloride, 1,1,1-trichloroethane, carbon tetrachloride, and the chlorinated fluorocarbons; and sludges from the recovery of these solvents in degreasing operations.	(T)
F002	The spent halogenated solvents, tetrachloroethylene, methylene chloride, trichloroethylene, 1,1,1-trichloroethane, chlorobenzene, 1,1,2-trichloro-1,2,2-trifluoroethane, o-dichlorobenzene, trichlorofluoromethane and the still bottoms from the recovery of these solvents.	(T)
F003	The spent non-halogenated solvents, xylene, acetone, ethyl acetate, ethyl benzene, ethyl ether, n-butyl alcohol, cyclohexanone, and the still bottoms from the recovery of these solvents.	(I)
F004	The spent non-halogenated solvents, cresols and cresylic acid, nitrobenzene, and the still bottoms from the recovery of these solvents	(T)
F005	The spent non-halogenated solvents, methanol, toluene, methyl ethyl ketone, methyl isobutyl ketone, carbon disulfide, isobutanol, pyridine and the still bottoms from the recovery of these solvents.	(I, T)
F006	Wastewater treatment sludges from electroplating operations	(T)
F007	Spent plating bath solutions from electroplating operations	(R)
F008	Plating bath sludges from the bottom of plating baths from electroplating operations	(R)
F009	Spent stripping and cleaning bath solutions from electroplating operations	(R)
F010	Quenching bath sludge from oil baths from metal heat treating operations	(R)
F011	Spent solutions from salt bath pot cleaning from metal heat treating operations	(R)
F012	Quenching wastewater treatment sludges from metal heat treating operations	(T)
F013	Flotation tailings from selective flotation from mineral metals recovery operations	(T)
F014	Cyanidation wastewater treatment tailing pond sediment from mineral metals recovery operations	(T)
F015	Spent cyanide bath solutions from mineral metals recovery operations	(R, T)
F016	Dewatered air pollution control scrubber sludges from coke ovens and blast furnaces	(T)

§ 261.32 Hazardous waste from specific sources.

Industry and EPA hazardous waste No.	Hazardous waste	Hazard code
Wood Preservation: K001	Bottom sediment sludge from the treatment of wastewaters from wood preserving processes that use creosote and/or pentachlorophenol	(T)
Inorganic Pigments:		
K002	Wastewater treatment sludge from the production of chrome yellow and orange pigments	(T)
K003	Wastewater treatment sludge from the production of molybdate orange pigments	(T)
K004	Wastewater treatment sludge from the production of zinc yellow pigments	(T)
K005	Wastewater treatment sludge from the production of chrome green pigments	(T)
K006	Wastewater treatment sludge from the production of chrome oxide green pigments (anhydrous and hydrated)	(T)
K007	Wastewater treatment sludge from the production of iron blue pigments	(T)
K008	Oven residue from the production of chrome oxide green pigments	(T)
Organic Chemicals:		
K009	Distillation bottoms from the production of acetaldehyde from ethylene	(T)
K010	Distillation side cuts from the production of acetaldehyde from ethylene	(T)
K011	Bottom stream from the wastewater stripper in the production of acrylonitrile	(R, T)
K012	Still bottoms from the final purification of acrylonitrile in the production of acrylonitrile	(T)
K013	Bottom stream from the acetonitrile column in the production of acrylonitrile	(R, T)
K014	Bottoms from the acetronitrile purification column in the production of acrylonitrile	(T)
K015	Still bottoms from the distillation of benzyl chloride	(T)
K016	Heavy ends or distillation residues from the production of carbon tetrachloride	(T)
K017	Heavy ends (still bottoms) from the purification column in the production of epichlorohydrin	(T)
K018	Heavy ends from fractionation in ethyl chloride production	(T)
K019	Heavy ends from the distillation of ethylene dichloride in ethylene dichloride production	(T)
K020	Heavy ends from the distillation of vinyl chloride in vinyl chloride monomer production	(T)
K021	Aqueous spent antimony catalyst waste from fluoromethanes production	(T)
K022	Distillation bottom tars from the production of phenol/acetone from cumene	(T)
K023	Distillation light ends from the production of phthalic anhydride from naphthalene	(T)
K024	Distillation bottoms from the production of phthalic anhydride from naphthalene	(T)
K025	Distillation bottoms from the production of nitrobenzene by the nitration of benzene	(T)
K026	Stripping still tails from the production of methyl ethyl pyridines	(T)
K027	Centrifuge residue from toluene diisocyanate production	(R)
K028	Spent catalyst from the hydrochlorinator reactor in the production of 1,1,1-trichloroethane	(T)
K029	Waste from the product stream stripper in the production of 1,1,1-trichloroethane	(T)
K030	Column bottoms or heavy ends from the combined production of trichloroethylene and perchloroethylene	(T)
Pesticides:		
K031	By-products salts generated in the production of MSMA and cacodylic acid	(T)
K032	Wastewater treatment sludge from the production of chlordane	(T)
K033	Wastewater and scrub water from the chlorination of cyclopentadiene in the production of chlordane	(T)
K034	Filter solids from the filtration of hexachlorocyclopentadiene in the production of chlordane	(T)
K035	Wastewater treatment sludges generated in the production of creosote	(T)
K036	Still bottoms from toluene reclamation distillation in the production of disulfoton	(T)
K037	Wastewater treatment sludges from the production of disulfoton	(T)
K038	Wastewater from the washing and stripping of phorate production	(T)
K039	Filter cake from the filtration of diethylphosphorodithoric acid in the production of phorate	(T)
K040	Wastewater treatment sludge from the production of phorate	(T)
K041	Wastewater treatment sludge from the production of toxaphene	(T)
K042	Heavy ends or distillation residues from the distillation of tetrachlorobenzene in the production of 2,4,5-T	(T)
K043	2,6-Dichlorophenol waste from the production of 2,4-D	(T)
Explosives:		
K044	Wastewater treatment sludges from the manufacturing and processing of explosives	(R)
K045	Spent carbon from the treatment of wastewater containing explosives	(R)
K046	Wastewater treatment sludges from the manufacturing, formulation and loading of lead-based initiating compounds	(T)
K047	Pink/red water from TNT operations	(R)
Petroleum Refining:		
K048	Dissolved air flotation (DAF) float from the petroleum refining industry	(T)
K049	Slop oil emulsion solids from the petroleum refining industry	(T)
K050	Heat exchanger bundle cleaning sludge from the petroleum refining industry	(T)
K051	API separator sludge from the petroleum refining industry	(T)
K052	Tank bottoms (leaded) from the petroleum refining industry	(T)
Leather Tanning Finishing:		
K053	Chrome (blue) trimmings generated by the following subcategories of the leather tanning and finishing industry: hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; retan/wet finish; no beamhouse; through-the-blue; and shearing.	(T)

§ 261.32 Hazardous waste from specific sources.—Continued

Industry and EPA hazardous waste No.	Hazardous waste	Hazard code
K054	Chrome (blue) shavings generated by the following subcategories of the leather tanning and finishing industry: hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; retan/wet finish; no beamhouse; through-the-blue; and shearling.	(T)
K055	Buffing dust generated by the following subcategories of the leather tanning and finishing industry: hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; retan/wet finish; no beamhouse; and through-the-blue.	(T)
K056	Sewer screenings generated by the following subcategories of the leather tanning and finishing industry: hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; retan/wet finish; no beamhouse; through-the-blue; and shearling.	(T)
K057	Wastewater treatment sludges generated by the following subcategories of the leather tanning and finishing industry: hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; retan/wet finish; no beamhouse; through-the-blue and shearling.	(T)
K058	Wastewater treatment sludges generated by the following subcategories of the leather tanning and finishing industry: hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; and through-the-blue.	(R, T)
K059	Wastewater treatment sludges generated by the following subcategory of the leather tanning and finishing industry: hair save/non-chrome tan/retan/wet finish.	(R)
Iron and Steel:		
K060	Ammonia still lime sludge from coking operations	(T)
K061	Emission control dust/sludge from the electric furnace production of steel	(T)
K062	Spent pickle liquor from steel finishing operations	(C, T)
K063	Sludge from lime treatment of spent pickle liquor from steel finishing operations	(T)
Primary Copper: K064	Acid plant blowdown slurry/sludge resulting from the thickening of blowdown slurry from primary copper production	(T)
Primary Lead: K065	Surface impoundment solids contained in and dredged from surface impoundments at primary lead smelting facilities	(T)
Primary Zinc:		
K066	Sludge from treatment of process wastewater and/or acid plant blowdown from primary zinc production	(T)
K067	Electrolytic anode slimes/sludges from primary zinc production	(T)
K068	Cadmium plant leach residue (iron oxide) from primary zinc production	(T)
Secondary Lead: K069	Emission control dust/sludge from secondary lead smelting	(T)

Also: K073, K095, K096

§ 261.33 Discarded Commercial Chemical Products, Off-Specification Species, Containers, and Spill Residues Thereof.

The following materials or items are hazardous wastes if and when they are discarded or intended to be discarded:

(a) Any commercial chemical product, or manufacturing chemical intermediate having the generic name listed in paragraphs (e) or (f) of this section.

(b) Any off-specification commercial chemical product or manufacturing chemical intermediate which, if it met specifications, would have the generic name listed in paragraphs (e) or (f) of this section.

(c) Any container or inner liner removed from a container that has been used to hold any commercial chemical product or manufacturing chemical intermediate having the generic name listed in paragraph (e) of this section, unless:

(1) The container or inner liner has been triple rinsed using a solvent, capable of removing the commercial chemical product or manufacturing chemical intermediate;

(2) The container or inner liner has been cleaned by another method that has been shown in the scientific literature, or by tests conducted by the generator, to achieve equivalent removal; or

(3) In the case of a container, the inner liner that prevented contact of the commercial chemical product or manufacturing chemical intermediate with the container, has been removed.

(d) Any residue or contaminated soil, water or other debris resulting from the cleanup of a spill, into or on any land or water, of any commercial chemical product or manufacturing chemical intermediate having the generic name listed in paragraphs (e) or (f) of this Section.

[Comment: The phrase "commercial chemical product or manufacturing chemical intermediate having the generic name listed in. . ." refers to a chemical substance which is manufactured or formulated for commercial or manufacturing use. It does not refer to a material, such as a manufacturing process waste, that contains any of the substances listed in paragraphs (e) or (f). Where a manufacturing process waste is deemed to be a hazardous waste because it contains a substance listed in paragraphs (e) or (f), such waste will be listed in either §§ 261.31 or 261.32 or will be identified as a hazardous waste by the characteristics set forth in Subpart C of this Part.]

(e) The commercial chemical products or manufacturing chemical intermediates, referred to in paragraphs (a) through (d) of this section, are identified as acute hazardous wastes (H) and are subject to the small quantity exclusion defined in § 261.5(c). These wastes and their corresponding EPA Hazardous Waste Numbers are:

Hazardous waste No.	Substance [1]
	1080 see P058
	1081 see P057
	(Acetato)phenylmercury see P092
	Acetone cyanohydrin see P069
P001	3-(alpha-Acetonylbenzyl)-4-hydroxycoumarin and salts
P002	1-Acetyl-2-thiourea
P003	Acrolein
	Agarin see P007
	Agrosan GN 5 see P092
	Aldicarb see P069
	Aldrin see P048

—Continued

Hazardous waste No.	Substance [1]
P004	Aldrin
	Algimycin see P092
P005	Allyl alcohol
P006	Aluminum phosphide (R)
	ALVIT see P037
	Aminoethylene see P054
P007	5-(Aminomethyl)-3-isoxazolol
P008	4-Aminopyridine
	Ammonium metavanadate see P119
P009	Ammonium picrate (R)
	ANTIMUCIN WDR see P092
	ANTURAT see P073
	AQUATHOL see P088
	ARETIT see P020
P010	Arsenic acid
P011	Arsenic pentoxide
P012	Arsenic trioxide
	Athrombin see P001
	AVITROL see P006
	Aziridene see P054
	AZOFOS see P061
	Azophos see P061
	BANTU see P072
P013	Barium cyanide
	BASENITE see P020
	BCME see P016
P014	Benzenethiol
	Benzoepin see P050
P015	Beryllium dust
P016	Bis(chloromethyl) ether
	BLADAN-M see P071
P017	Bromoacetone
P018	Brucine
P019	2-Butanone peroxide
	BUFEN see P092
	Butaphene see P020
P020	2-sec-Butyl-4,6-dinitrophenol
P021	Calcium cyanide
	CALDON see P020
P022	Carbon disulfide
	CERESAN see P092
	CERESAN UNIVERSAL see P092
	CHEMOX GENERAL see P020
	CHEMOX P.E. see P020
	CHEM-TOL see P090
P023	Chloroacetaldehyde
P024	p-Chloroaniline
P025	1-(p-Chlorobenzoyl)-5-methoxy-2-methylindole-3-acetic acid
P026	1-(o-Chlorophenyl)thiourea
P027	3-Chloropropionitrile
P028	alpha-Chlorotoluene
P029	Copper cyanide
	CRETOX see P106
	Coumadin see P001
	Coumafen see P001
P030	Cyanides

Hazardous waste No.	Substance [1]
P031	Cyanogen
P032	Cyanogen bromide
P033	Cyanogen chloride
	Cyclodan see P050
P034	2-Cyclohexyl-4,6-dinitrophenol
	D-CON see P001
	DETHMOR see P001
	DETHNEL see P001
	DFP see P043
P035	2,4-Dichlorophenoxyacetic acid (2,4-D)
P036	Dichlorophenylarsine
	Dicyanogen see P031
P037	Dieldrin
	DIELDREX see P037
P038	Diethylarsine
P039	0,0-Diethyl-S-[2-(ethylthio)ethyl]ester of phosphorothioic acid
P040	0,0-Diethyl-0-(2-pyrazinyl)phosphorothioate
P041	0,0-Diethyl phosphoric acid, 0-p-nitrophenyl ester
P042	3,4-Dihydroxy-alpha-(methylamino)-methyl benzyl alcohol
P043	Di-isopropylfluorophosphate
	DIMETATE see P044
	1,4:5,8-Dimethanonaphthalene, 1,2,3,4,10,10-hexachloro-1,4,4a,5,8,8a-hexahydro endo, endo see P060
P044	Dimethoate
P045	3,3-Dimethyl-1-(methylthio)-2-butanone-O-[(methylamino)carbonyl] oxime
P046	alpha,alpha-Dimethylphenethylamine
	Dinitrocyclohexylphenol see P034
P047	4,6-Dinitro-o-cresol and salts
P048	2,4-Dinitrophenol
	DINOSEB see P020
	DINOSEBE see P020
	Disulfoton see P039
P049	2,4-Dithiobiuret
	DNBP see P020
	DOLCO MOUSE CEREAL see P108
	DOW GENERAL see P020
	DOW GENERAL WEED KILLER see P020
	DOW SELECTIVE WEED KILLER see P020
	DOWICIDE G see P090
	DYANACIDE see P092
	EASTERN STATES DUOCIDE see P001
	ELGETOL see P020
P050	Endosulfan
P051	Endrin
	Epinephrine see P042
P052	Ethylcyanide
P053	Ethylenediamine
P054	Ethyleneimine
	FASCO FASCRAT POWDER see P001
	FEMMA see P091
P055	Ferric cyanide
P056	Fluorine
P057	2-Fluoroacetamide
P058	Fluoroacetic acid, sodium salt
	FOLODOL-80 see P071
	FOLODOL M see P071
	FOSFERNO M 50 see P071
	FRATOL see P058
	Fulminate of mercury see P065
	FUNGITOX OR see P092
	FUSSOF see P057
	GALLOTOX see P092
	GEARPHOS see P071
	GERUTOX see P020
P059	Heptachlor
P060	1,2,3,4,10,10-Hexachloro-1,4,4a,5,8,8a-hexahydro-1,4:5,8-endo, endo-dimethanonaphthalene
	1,4,5,6,7,7-Hexachloro-cyclic-5-norbornene-2,3-dimethanol sulfite see P050
P061	Hexachloropropene
P062	Hexaethyl tetraphosphate
	HOSTAQUICK see P092
	HOSTAQUIK see P092
	Hydrazomethane see P068
P063	Hydrocyanic acid
	ILLOXOL see P037
	INDOCI see P025
	Indomethacin see P025
	INSECTOPHENE see P050
	Isodrin see P060
P064	Isocyanic acid, methyl ester
	KILOSEB see P020
	KOP-THIODAN see P050
	KWIK-KIL see P108
	KWIKSAN see P092
	KUMADER see P001
	KYPFARIN see P001
	LEYTOSAN see P092
	LIQUIPHENE see P092
	MALIK see P050
	MAREVAN see P001
	MAR-FRIN see P001
	MARTIN'D MAR-FRIN see P001
	MAVERAN see P001
	MEGATOX see P005
P065	Mercury fulminate
	MERSOLITE see P092
	METACID 50 see P071
	METAFOS see P071
	METAPHOR see P071
	METAPHOS see P071
	METASOL 30 see P092
P066	Methomyl
P067	2-Methylaziridine
	METHYL-E 605 see P071
P068	Methyl hydrazine
	Methyl isocyanate see P064
P069	2-Methyllactonitrile
P070	2-Methyl-2-(methylthio)propionaldehyde-o-(methylcarbonyl) oxime
	METHYL NIRON see P042
P071	Methyl parathion
	METRON see P071
	MOLE DEATH see P108
	MOUSE-NOTS see P108
	MOUSE-RID see P108
	MOUSE-TOX see P108
	MUSCIMOL see P007
P072	1-Naphthyl-2-thiourea
P073	Nickel carbonyl
P074	Nickel cyanide
P075	Nicotine and salts
P076	Nitric oxide
P077	p-Nitroaniline
P078	Nitrogen dioxide
P079	Nitrogen peroxide
P080	Nitrogen tetroxide
P081	Nitroglycerine (R)
P082	N-Nitrosodimethylamine
P083	N-Nitrosodiphenylamine
P084	N-Nitrosomethylvinylamine
	NYLMERATE see P092
	OCTALOX see P037
P085	Octamethylpyrophosphoramide
	OCTAN see P092
P086	Oleyl alcohol condensed with 2 moles ethylene oxide
	OMPA see P085
	OMPACIDE see P085
	OMPAX see P085
P087	Osmium tetroxide
P088	7-Oxabicyclo[2.2.1]heptane-2,3-dicarboxylic acid
	PANTARFIN see P001
	PANORAM D-31 see P037
	PANTHERINE see P007
	PANWARFIN see P001
P089	Parathion
	PCP see P090
	PENNCAP-M see P071
	PENOXYL CARBON N see P048
P090	Pentachlorophenol
	Pentachlorophenate see P090
	PENTA-KILL see P090
	PENTASOL see P090
	PENWAR see P090
	PERMICIDE see P090
	PERMAGUARD see P090
	PERMATOX see P090
	PERMITE see P060
	PERTOX see P090
	PESTOX III see P085
	PHENMAD see P092
	PHENOTAN see P020
P091	Phenyl dichloroarsine
	Phenyl mercaptan see P014
P092	Phenylmercury acetate
P093	N-Phenylthiourea
	PHILIPS 1861 see P008
	PHIX see P092
P094	Phorate
P095	Phosgene
P096	Phosphine
P097	Phosphorothioic acid, 0,0-dimethyl ester, 0-ester with N,N-dimethyl benzene sulfonamide
	Phosphorothioic acid 0,0-dimethyl-0-(p-nitrophenyl) ester see P071
	PIED PIPER MOUSE SEED see P108
P098	Potassium cyanide
P099	Potassium silver cyanide
	PREMERGE see P020
P100	1,2-Propanediol
	Propargyl alcohol see P102
P101	Propionitrile
P102	2-Propyn-1-ol
	PROTHROMADIN See P001
	QUICKSAM see P092
	QUINTOX see P037
	RAT AND MICE BAIT see P001
	RAT-A-WAY see P001
	RAT-B-GON see P001
	RAT-O-CIDE #2 see P001
	RAT-GUARD see P001
	RAT-KILL see P001
	RAT-MIX see P001
	RATS-NO-MORE see P001
	RAT-OLA see P001
	RATOREX see P001
	RATTUNAL see P001
	RAT-TROL see P001
	RO-DETH see P001
	RO-DEX see P108
	ROSEX see P001
	ROUGH & READY MOUSE MIX see P001
	SANASEED see P108
	SANTOBRITE see P090
	SANTOPHEN see P090
	SANTOPHEN 20 see P090
	SCHRADAN see P085
P103	Selenourea
P104	Silver Cyanide
	SMITE see P105
	SPARIC see P020.
	SPOR-KIL see P092
	SPRAY-TROL BRAND RODEN-TROL see P001
	SPURGE see P020
P105	Sodium azide
	Sodium coumadin see P001
P106	Sodium cyanide
	Sodium fluoroacetate see P058
	SODIUM WARFARIN see P001
	SOLFARIN see P001
	SOLFOBLACK BB see P048
	SOLFOBLACK SB see P048
P107	Strontium sulfide
P108	Strychnine and salts
	SUBTEX see P020
	SYSTAM see P085
	TAG FUNGICIDE see P092
	TEKWAISA see P071
	TEMIC see P070
	TEMIK see P070
	TERM-I-TROL see P090
P109	Tetraethyldithiopyrophosphate
P110	Tetraethyl lead
P111	Tetraethylpyrophosphate
P112	Tetranitromethane
	Tetraphosphoric acid, hexaethyl ester see P062
	TETROSULFUR BLACK PB see P048
	TETROSULPHUR PBR see P048
P113	Thallic oxide
	Thallium peroxide see P113
P114	Thallium selenite
P115	Thallium (I) sulfate
	THIFOR see P092
	THIMUL see P092
	THIODAN see P050
	THIOFOR see P050
	THIOMUL see P050
	THIONEX see P050
	THIOPHENIT see P071
P116	Thiosemicarbazide
	Thiosulfan tional see P050
P117	Thiuram
	THOMPSON'S WOOD FIX see P090
	TIOVEL see P050
P118	Trichloromethanethiol
	TWIN LIGHT RAT AWAY see P001
	USAF RH-8 see P069
	USAF EK-4890 see P002
P119	Vanadic acid, ammonium salt
P120	Vanadium pentoxide
	VOFATOX see P071
	WANADU see P120
	WARCOUMIN see P001
	WARFARIN SODIUM see P001
	WARFICIDE see P001
	WOFOTOX see P072
	YANOCK see P057
	YASOKNOCK see P058
	ZIARNIK see P092
P121	Zinc cyanide
P122	Zinc phosphide (R,T)
	ZOOCOUMARIN see P001

[1] The Agency included those trade names of which it was aware; an omission of a trade name does not imply that the omitted material is not hazardous. The material is hazardous if it is listed under its generic name.

(f) The commercial chemical products or manufacturing chemical intermediates, referred to in paragraphs (a), (b) and (d) of this section, are identified as toxic wastes (T) unless otherwise designated and are subject to the small quantity exclusion defined in § 261.5 (a) and (b). These wastes and their corresponding EPA Hazardous Waste Numbers are:

Hazardous Waste No.	Substance[1]
	AAF see U005
U001	Acetaldehyde
U002	Acetone (I)
U003	Acetonitrile (I,T)
U004	Acetophenone
U005	2-Acetylaminoflourene
U006	Acetyl chloride (C,T)
U007	Acrylamide
	Acetylene tetrachloride see U209
	Acetylene trichloride see U228
U008	Acrylic acid (I)
U009	Acrylonitrile
	AEROTHENE TT see U226
	3-Amino-5-(p-acetamidophenyl)-1H-1,2,4-triazole, hydrate see U011
U010	6-Amino-1,1a,2,8,8a,8b-hexahydro-8-(hydroxymethyl)8-methoxy-5-methylcarbamate azirino(2',3':3,4) pyrrolo(1,2-a) indole-4, 7-dione (ester)
U011	Amitrole
U012	Aniline (I)
U013	Asbestos
U014	Auramine
U015	Azaserine
U016	Benz[c]acridine
U017	Benzal chloride
U018	Benz[a]anthracene
U019	Benzene
U020	Benzenesulfonyl chloride (C,R)
U021	Benzidine
	1,2-Benzisothiazolin-3-one, 1,1-dioxide see U202
	Benzo[a]anthracene see U018
U022	Benzo[a]pyrene
U023	Benzotrichloride (C,R,T)
U024	Bis(2-chloroethoxy)methane
U025	Bis(2-chloroethyl) ether
U026	N,N-Bis(2-chloroethyl)-2-naphthylamine
U027	Bis(2-chloroisopropyl) ether
U028	Bis(2-ethylhexyl) phthalate
U029	Bromomethane
U030	4-Bromophenyl phenyl ether
U031	n-Butyl alcohol (I)
U032	Calcium chromate
	Carbolic acid see U188
	Carbon tetrachloride see U211
U033	Carbonyl fluoride
U034	Chloral
U035	Chlorambucil
U036	Chlordane
U037	Chlorobenzene
U038	Chlorobenzilate
U039	p-Chloro-m-cresol
U040	Chlorodibromomethane
U041	1-Chloro-2,3-epoxypropane
	CHLOROETHENE NU see U226
U042	Chloroethyl vinyl ether
U043	Chloroethene
U044	Chloroform (I,T)
U045	Chloromethane (I,T)
U046	Chloromethyl methyl ether
U047	2-Chloronaphthalene
U048	2-Chlorophenol
U049	4-Chloro-o-toluidine hydrochloride
U050	Chrysene
	C.I. 23060 see U073
U051	Cresote
U052	Cresols
U053	Crotonaldehyde
U054	Cresylic acid
U055	Cumene
	Cyanomethane see U003
U056	Cyclohexane (I)
U057	Cyclohexanone (I)
U058	Cyclophosphamide
U059	Daunomycin
U060	DDD
U061	DDT
U062	Diallate
U063	Dibenz[a,h]anthracene
	Dibenzo[a,h]anthracene see U063
U064	Dibenzo[a,i]pyrene
U065	Dibromochloromethane
U066	1,2-Dibromo-3-chloropropane
U067	1,2-Dibromoethane
U068	Dibromomethane
U069	Di-n-butyl phthalate
U070	1,2-Dichlorobenzene
U071	1,3-Dichlorobenzene
U072	1,4-Dichlorobenzene
U073	3,3'-Dichlorobenzidine
U074	1,4-Dichloro-2-butene
	3,3'-Dichloro-4,4'-diaminobiphenyl see U073
U075	Dichlorodifluoromethane
U076	1,1-Dichloroethane
U077	1,2-Dichloroethane
U078	1,1-Dichloroethylene
U079	1,2-trans-dichloroethylene
U080	Dichloromethane
	Dichloromethylbenzene see U017
U081	2,4-Dichlorophenol
U082	2,6-Dichlorophenol
U083	1,2-Dichloropropane
U084	1,3-Dichloropropene
U085	Diepoxybutane (I,T)
U086	1,2-Diethylhydrazine
U087	0,0-Diethyl-S-methyl ester of phosphorodithioic acid
U088	Diethyl phthalate
U089	Diethylstilbestrol
U090	Dihydrosafrole
U091	3,3'-Dimethoxybenzidine
U092	Dimethylamine (I)
U093	p-Dimethylaminoazobenzene
U094	7,12-Dimethylbenz[a]anthracene
U095	3,3'-Dimethylbenzidine
U096	alpha,alpha-Dimethylbenzylhydroperoxide (R)
U097	Dimethylcarbamoyl chloride
U098	1,1-Dimethylhydrazine
U099	1,2-Dimethylhydrazine
U100	Dimethylnitrosoamine
U101	2,4-Dimethylphenol
U102	Dimethyl phthalate
U103	Dimethyl sulfate
U104	2,4-Dinitrophenol
U105	2,4-Dinitrotoluene
U106	2,6-Dinitrotoluene
U107	Di-n-octyl phthalate
U108	1,4-Dioxane
U109	1,2-Diphenylhydrazine
U110	Dipropylamine (I)
U111	Di-n-propylnitrosamine
	EBDC see U114
	1,4-Epoxybutane see U213
U112	Ethyl acetate (I)
U113	Ethyl acrylate (I)
U114	Ethylenebisdithiocarbamate
U115	Ethylene oxide (I,T)
U116	Ethylene thiourea
U117	Ethyl ether (I,T)
U118	Ethylmethacrylate
U119	Ethyl methanesulfonate
	Ethylnitrile see U003
	Firemaster T23P see U235
U120	Fluoranthene
U121	Fluorotrichloromethane
U122	Formaldehyde
U123	Formic acid (C,T)
U124	Furan (I)
U125	Furfural (I)
U126	Glycidylaldehyde
U127	Hexachlorobenzene
U128	Hexachlorobutadiene
U129	Hexachlorocyclohexane
U130	Hexachlorocyclopentadiene
U131	Hexachloroethane
U132	Hexachlorophene
U133	Hydrazine (R,T)
U134	Hydrofluoric acid (C,T)
U135	Hydrogen sulfide
	Hydroxybenzene see U188
U136	Hydroxydimethyl arsine oxide
	4,4'-(imidocarbonyl)bis(N,N-dimethyl)aniline see U014
U137	Indeno(1,2,3-cd)pyrene
U138	Iodomethane
U139	Iron Dextran
U140	Isobutyl alcohol
U141	Isosafrole
U142	Kepone
U143	Lasiocarpine
U144	Lead acetate
U145	Lead phosphate
U146	Lead subacetate
U147	Maleic anhydride
U148	Maleic hydrazide
U149	Malononitrile
	MEK Peroxide see U160
U150	Melphalan
U151	Mercury
U152	Methacrylonitrile
U153	Methanethiol
U154	Methanol
U155	Methapyrilene
	Methyl alcohol see U154
U156	Methyl chlorocarbonate
	Methyl chloroform see U226
U157	3-Methylcholanthrene
	Methyl chloroformate see U156
U158	4,4'-Methylene-bis-(2-chloroaniline)
U159	Methyl ethyl ketone (MEK) (I,T)
U160	Methyl ethyl ketone peroxide (R)
	Methyl iodide see U138
U161	Methyl isobutyl ketone
U162	Methyl methacrylate (R,T)
U163	N-Methyl-N'-nitro-N-nitrosoguanidine
U164	Methylthiouracil
	Mitomycin C see U010
U165	Naphthalene
U166	1,4-Naphthoquinone
U167	1-Naphthylamine
U168	2-Naphthylamine
U169	Nitrobenzene (I,T)
	Nitrobenzol see U169
U170	4-Nitrophenol
U171	2-Nitropropane (I)
U172	N-Nitrosodi-n-butylamine
U173	N-Nitrosodiethanolamine
U174	N-Nitrosodiethylamine
U175	N-Nitrosodi-n-propylamine
U176	N-Nitroso-n-ethylurea
U177	N-Nitroso-n-methylurea
U178	N-Nitroso-n-methylurethane
U179	N-Nitrosopiperidine
U180	N-Nitrosopyrrolidine
U181	5-Nitro-o-toluidine
U182	Paraldehyde
	PCNB see U185
U183	Pentachlorobenzene
U184	Pentachloroethane
U185	Pentachloronitrobenzene
U186	1,3-Pentadiene (I)
	Perc see U210
	Perchlorethylene see U210
U187	Phenacetin
U188	Phenol
U189	Phosphorous sulfide (R)
U190	Phthalic anhydride
U191	2-Picoline
U192	Pronamide
U193	1,3-Propane sultone
U194	n-Propylamine (I)
U196	Pyridine
U197	Quinones
U200	Reserpine
U201	Resorcinol
U202	Saccharin
U203	Safrole
U204	Selenious acid
U205	Selenium sulfide (R,T)
	Silvex see U233
U206	Streptozotocin
	2,4,5-T see U232
U207	1,2,4,5-Tetrachlorobenzene
U208	1,1,1,2-Tetrachloroethane
U209	1,1,2,2-Tetrachloroethane
U210	Tetrachloroethene
	Tetrachloroethylene see U210
U211	Tetrachloromethane
U212	2,3,4,6-Tetrachlorophenol
U213	Tetrahydrofuran (I)
U214	Thallium (I) acetate
U215	Thallium (I) carbonate
U216	Thallium (I) chloride
U217	Thallium (I) nitrate
U218	Thioacetamide
U219	Thiourea
U220	Toluene
U221	Toluenediamine
U222	o-Toluidine hydrochloride

Hazardous Waste No.	Substance[1]
U223	Toluene diisocyanate
U224	Toxaphene
	2,4,5-TP see U233
U225	Tribromomethane
U226	1,1,1-Trichloroethane
U227	1,1,2-Trichloroethane
U228	Trichloroethene
	Trichloroethylene see U228
U229	Trichlorofluoromethane
U230	2,4,5-Trichlorophenol
U231	2,4,6-Trichlorophenol
U232	2,4,5-Trichlorophenoxyacetic acid
U233	2,4,5-Trichlorophenoxypropionic acid alpha, alpha, alpha- Trichlorotoluene see U023
	TRI-CLENE see U228
U234	Trinitrobenzene (R,T)
U235	Tris(2,3-dibromopropyl) phosphate
U236	Trypan blue
U237	Uracil mustard
U238	Urethane
	Vinyl chloride see U043
	Vinylidene chloride see U078
U239	Xylene

[1] The Agency included those trade names of which it was aware; an omission of a trade name does not imply that it is not hazardous. The material is hazardous if it is listed under its generic name.

Appendix I—Representative Sampling Methods

The methods and equipment used for sampling waste materials will vary with the form and consistency of the waste materials to be sampled. Samples collected using the sampling protocols listed below, for sampling waste with properties similar to the indicated materials, will be considered by the Agency to be representative of the waste.

Extremely viscous liquid—ASTM Standard D140–70 Crushed or powdered material—ASTM Standard D346–75 Soil or rock-like material—ASTM Standard D420–69 Soil-like material—ASTM Standard D1452–65

Fly Ash-like material—ASTM Standard D2234–76 [ASTM Standards are available from ASTM, 1916 Race St., Philadelphia, PA 19103]

Containerized liquid wastes—"COLIWASA" described in "Test Methods for the Evaluation of Solid Waste, Physical/Chemical Methods," [1] U.S. Environmental Protection Agency, Office of Solid Waste, Washington, D.C. 20460. [Copies may be obtained from Solid Waste Information, U.S. Environmental Protection Agency, 26 W. St. Clair St., Cincinnati, Ohio 45268]

Liquid waste in pits, ponds, lagoons, and similar reservoirs.—"Pond Sampler" described in "Test Methods for the Evaluation of Solid Waste, Physical/Chemical Methods." [1]

This manual also contains additional information on application of these protocols.

[1] These methods are also described in "Samplers and Sampling Procedures for Hazardous Waste Streams," EPA 600/2-80-018, January 1980.

Appendix II— EP Toxicity Test Procedure

A. Extraction Procedure (EP)

1. A representative sample of the waste to be tested (minimum size 100 grams) should be obtained using the methods specified in Appendix I or any other methods capable of yielding a representative sample within the meaning of Part 260. [For detailed guidance on conducting the various aspects of the EP see "Test Methods for the Evaluation of Solid Waste, Physical/Chemical Methods," SW–846, U.S. Environmental Protection Agency Office of Solid Waste, Washington, D.C. 20460.[1]]

2. The sample should be separated into its component liquid and solid phases using the method described in "Separation Procedure" below. If the solid residue [2] obtained using this method totals less than 0.5% of the original weight of the waste, the residue can be discarded and the operator should treat the liquid phase as the extract and proceed immediately to Step 8.

3. The solid material obtained from the Separation Procedure should be evaluated for its particle size. If the solid material has a surface area per gram of material equal to, or greater than, 3.1 cm^2 or passes through a 9.5 mm (0.375 inch) standard sieve, the operator should proceed to Step 4. If the surface area is smaller or the particle size larger than specified above, the solid material should be prepared for extraction by crushing, cutting or grinding the material so that it passes through a 9.5 mm (0.375 inch) sieve or, if the material is in a single piece, by subjecting the material to the "Structural Integrity Procedure" described below.

4. The solid material obtained in Step 3 should be weighed and placed in an extractor with 16 times its weight of deionized water. Do not allow the material to dry prior to weighing. For purposes of this test, an acceptable extractor is one which will impart sufficient agitation to the mixture to not only prevent stratification of the sample and extraction fluid but also insure that all sample surfaces are continously brought into contact with well mixed extraction fluid.

5. After the solid material and deionized water are placed in the extractor, the operator should begin agitation and measure the pH of the solution in the extractor. If the pH is greater than 5.0, the pH of the solution should be decreased to 5.0 ± 0.2 by adding 0.5 N acetic acid. If the pH is equal to or less than 5.0, no acetic acid should be added. The pH of the solution should be monitored, as described below, during the course of the extraction and if the pH rises above 5.0 0.5N acetic acid should be added to bring the pH down to 5.0 ± 0.2. However, in no event shall the aggregate amount of acid added to the solution exceed 4 ml of acid per gram of solid. The mixture should be agitated for 24 hours and maintained at 20°–40° C (68°–104° F) during this time. It is recommended that the operator monitor and adjust the pH during the course of the extraction with a device such as the Type 45–A pH Controller manufactured by Chemtrix, Inc., Hillsboro, Oregon 97123 or its equivalent, in conjunction with a metering pump and reservoir of 0.5N acetic acid. If such a system is not available, the following manual procedure shall be employed:

(a) A pH meter should be calibrated in accordance with the manufacturer's specifications.

(b) The pH of the solution should be checked and, if necessary, 0.5N acetic acid should be manually added to the extractor until the pH reaches 5.0 ± 0.2. The pH of the solution should be adjusted at 15, 30 and 60 minute intervals, moving to the next longer interval if the pH does not have to be adjusted more than 0.5N pH units.

(c) The adjustment procedure should be continued for at least 6 hours.

(d) If at the end of the 24-hour extraction period, the pH of the solution is not below 5.0 and the maximum amount of acid (4 ml per gram of solids) has not been added, the pH should be adjusted to 5.0 ± 0.2 and the extraction continued for an additional four hours, during which the pH should be adjusted at one hour intervals.

6. At the end of the 24 hour extraction period, deionized water should be added to the extractor in an amount determined by the following equation:

V = (20)(W) − 16(W) − A

V = ml deionized water to be added

W = weight in grams of solid charged to extractor

A = ml of 0.5N acetic acid added during extraction

7. The material in the extractor should be separated into its component liquid and solid phases as described under "Separation Procedure."

8. The liquids resulting from Steps 2 and 7 should be combined. This

[1] Copies may be obtained from Solid Waste Information, U.S. Environmental Protection Agency, 26 W. St. Clair Street, Cincinnati, Ohio 45268.

[2] The percent solids is determined by drying the filter pad at 80° C until it reaches constant weight and then calculating the percent solids using the following equation:

$$\frac{(\text{weight of pad + solid}) - (\text{tare weight of pad})}{\text{initial weight of sample}} \times 100 = \%\ \text{solids}$$

Attachment V.-

TEXAS DEPARTMENT OF WATER RESOURCES
1700 N. Congress Avenue
Austin, Texas

TEXAS WATER DEVELOPMENT BOARD
Louis A. Beecherl, Jr., Chairman
George W. McCleskey, Vice Chairman
Glen E. Roney
W. O. Bankston
Lonnie A. "Bo" Pilgrim
Louie Welch

Charles E. Nemir
Executive Director

TEXAS WATER COMMISSION
Lee B. M. Biggart, Chairman
Felix McDonald
John D. Stover

December 17, 1982

Ms. Karen Shewbart, Environmental Mgr.
Dow Chemical Company USA
P. O. Drawer K B-2616
Freeport, TX 77541

Dear Ms. Shewbart:

Re: Dow Chemical Company, USA, Texas Division, ISW Registration No. 30106

During the inspection in September, 1982, by Gail Corrigan of this Department, the status of the closed landfills and surface impoundments at your facility were discussed. It was noted from this discussion that chlorinated hydrocarbon contaminants from some of the closed facilities have been detected in the uppermost aquifers. As defined by the Texas Water Code Section 26.001, "waters of the state" includes both surface waters and groundwater, percolating or otherwise, inside the territorial limits of the state. Therefore, the uppermost aquifers on your facility are considered to be "waters of the state", subject to jurisdiction of Texas Department of Water Resources as declared by the Water Code, Section 5.011.

The prohibitions set forth in Section 26.121 of the Water Code state that no person may discharge or allow seepage of industrial waste into any water in the state without authorization from this Department. Thus, any release of industrial waste from the closed landfills or surface impoundments on your facility into the waters of the State would be a violation of this statute.

Pursuant to Section 26.015 of the Water Code, the following information should be forwarded to our office:

1. The locations and dimensions of all closed landfills and surface impoundments.

2. Analytical data from all monitor wells adjacent to or those monitoring closed land disposal/storage areas since January, 1981.

3. Monitor well information, including locations, depths, diameters and completion data on each well.

4. Types and concentrations of contaminants in the aquifers.

5. The extent, both vertical and horizontal, of contamination in the aquifers.

6. Measures that have been taken to contain and/or remove contaminants from the groundwater.

7. Measures that are planned and/or are being evaluated in order to eliminate any threat to the environment.

8. In addition to the information noted in items 1-7, we also request similar data be provided this office concerning groundwater contamination of which you are aware that may be occurring from any other facilities at the Texas Division including but not limited to process and storage areas.

Please respond in writing to this office by January 29, 1982, with the above requested information. If you have any questions on this matter, please contact Ms. Gail Corrigan at (713) 479-5981.

Sincerely,

Merton J Coloton

Merton J. Coloton
Supervisor, District 7

MJC/GC/jea

ATTACHMENT VI

original sent to Gary Schroeder

DOW CHEMICAL U.S.A.

TEXAS DIVISION
FREEPORT, TEXAS 77541

January 28, 1983

received E&E, 3-2-83

Mr. Merton Coloton
Supervisor, District 7
4301 Center Street
Deer Park, TX 77536

Dear Mr. Coloton:

This letter is in response to your letter of December 17, 1982 in regards to the status of the closed landfills and surface impoundments in Dow's Texas Division.

Dow has instituted a closed landfill and surface impoundment management program which includes evaluation, monitoring, and, where appropriate, remedial action to contain or remove contaminants from these sites.

We believe that this program will prevent any adverse impact to the environment from Dow's sites and will serve to protect the air, surface water, and underground drinking water supplies of the areas.

We would also like to emphasize that all of our data shows that there are no contaminants leaving our Texas Division property.

Location and Dimensions of Closed Landfills and Surface Impoundments

The enclosure entitled "Dow Texas Division Inactive Landfills and Surface Impoundments" includes maps and a narrative description giving the location and dimensions of each inactive landfill and surface impoundment in the Division.

Monitor Well Information and Analytical Results

The above-referenced enclosure contains the following information for each monitor well:

1) Monitor well description, including locations, depths, diameters, and completion data.

2) Analytical data from all monitor wells adjacent to or those monitoring closed land disposal/storage areas since January, 1981.

3) Sampling information including, where present, types and concentrations of contaminants.

Results of certain wells are not included in this monitoring well section. In certain instances shallow wells have been drilled into the landfills themselves, and these have been used for purposes other than monitoring (e.g. head profiles, recovery wells, etc.).

In addition, sampling and analysis of some contaminated monitoring wells adjacent to the A-41 landfill have been discontinued. All analyses of these wells to date are included. However, since we are using monitor well data to define the plume of contamination, we have replaced these wells with wells on the perimeter of the plume.

Extent of Contamination

In responding to questions regarding extent of contamination, we were somewhat confused by TDWR's terminology. Questions 4 and 5 of your letter adress aquifers, while 7 requested information on groundwater. The saturated clays and sands in the Freeport area do not meet the RCRA definition of an aquifer and there has been no contamination of an aquifer as defined by RCRA (40 CFR Part 260). Furthermore, the water in the clays in the vicinity of our sites is not useable since it contains more than 10,000 mg/L of TDS. We believe it is important to emphasize that no aquifer, useable or otherwise, has been contaminated or is threatened by contamination from our sites.

We are responding to these questions by addressing contamination of the saturated clays and sands adjacent to our sites.

The extent of contamination for each of the areas is as follows:

1. A-100 - This disposal area is more than 30 years old, and the disposal area itself is largely undefined. It is therefore difficult to determine exact amounts of movement. However, no contamination has been noted below (-50) feet. The disposal area is about 550' X 300'. Total amount of material contained is estimated to be approximately 500 tons. This area at one time was a sanitary landfill for the city of Freeport.

2. A-41 - This area was our most extensively used disposal area and is the area upon which we have focused most of our attention. We have an extensive monitoring and remedial program underway in this area to assess the extent of migration and to contain the materials. The following summarizes the extent of the migration:

   a) Chlorinated hydrocarbons (RCl's) were found to be more concentrated in the sand and silty-to-sandy clays in

the upper 20-30' of sediments adjacent to the A-41 Block. Penetrations of not more than 5' to 10' have been noted in the lower greenish clays underlying the sands and sandy-silty clays.

b) A separate RCl phase has been defined under the A-41 Block, and migration of this phase outside the perimeter of the landfill area has been noted and defined through our monitoring well program. The continuing migration of this phase is now being retarded by a remedial program in this area.

c) The downward movement is retarded by the clays. As stated previously, penetrations of not more than 5' to 10' have been noted into the continuous clay layer. We are confident that because of the removal of RCl's through remedial efforts and the absorptive properties of such clays, the contaminants will present no problems to the Chicot aquifer some 200 feet below this area.

d) Some mounding of groundwater, to elevations of +14', occurs in the A-41 Block. The maintenance of a proper cap in this area and the removal of groundwater will tend to minimize the horizontal velocity of the contaminants.

3. A-76 - From monitoring wells in this area, there is no indication of any migration outside of the impoundment area. These impoundments are approximately 20' deep and are clay-lined and clay-capped.

4. B-47 - Impoundments in this area are also clay-lined and clay-capped. Wells have been installed (Jan. 1983) to obtain data; however, no monitoring well data is available as yet to determine migration.

5. B-60 (Styrene Lagoons) - No monitoring wells have been placed in this area. However, analysis of surface water from the pits and shaker studies of styrene tars and water indicate low water solubility (<50 ppb) and would therefore predict very little groundwater contamination and movement.

Containment and Removal

Measures taken to contain and/or remove contamination from the groundwater are as follows:

Containment:

Starting in the early 1970's and continuing through the first quarter of 1980, when the use of disposal pits was discontinued, clay liners and caps were installed for containment purposes. Prior to closure, free liquids were removed by digging trenches to allow the settled solids to dewater and by "squeezing" the settled solids with compacted backfill. The last impoundment incorporated a permanent internal drain and sump to allow removal of collected liquids after the final crowned clay cap was applied.

Prior to the 1970's, disposal pits were constructed on grade with clay levees only. Free liquids were absorbed with backfill material prior to installation of a clay cap.

Removal:

A remedial program is underway in the A-41 Block. After extensive study, a system of recovery wells and monitoring wells is being operated for the purpose of control and removal of contaminants.

(Monitoring wells at the A-76 site do not indicate the need for remedial activity).

As noted above, a permanent drain has been installed in the B-47 disposal pit to continuously remove contaminants.

No other remedial work is currently indicated as being warranted.

Future Plans

Future plans for management of Dow's Texas Division waste disposal sites are as follows:

1. Monitor Wells

   a) Existing monitoring wells will be sampled and analyzed on a quarterly basis to assess the extent of horizontal and vertical migration.

   b) Installation of monitoring wells in B-47 area has been completed (3 wells). These wells will be analyzed on a monthly basis for 4 months to establish baseline data. After completion of baseline data gathering, sampling and analysis will be on a quarterly basis.

2. Recovery Wells

a) Remedial program in A-41 Block will be continued and upgraded.

b) Recovery of contaminants from the B-47 disposal pits will continue.

c) Monitoring well results will dictate further remedial activity.

We believe that this program of monitoring wells and recovery wells will keep any contamination well within Dow's property and eliminate any threat to the groundwater or surface water, as well as the useable aquifer in the vicinity.

Other Groundwater Contamination

We are unaware of instances of groundwater contamination in the Texas Division other than those described above. Our groundwater management program has focused on areas where contamination is most likely to occur, namely those areas where wastes were purposely placed.

K. L. Shewbart

K. L. Shewbart
Environmental Services

wf

Enclosures